

Cisco/сеанс цисководства — Urbanculture

[обратно к статье «Cisco»](#)

[Цены](#) · [сеанс цисководства](#)

Типичный сеанс цисководства

```
Router>enable
```

```
Router#show interfaces summary
```

```

*: interface is up
IHQ: pkts in input hold queue      IQD: pkts dropped from input queue
OHQ: pkts in output hold queue     OQD: pkts dropped from output queue
RXBS: rx rate (bits/sec)           RXPS: rx rate (pkts/sec)
TXBS: tx rate (bits/sec)           TXPS: tx rate (pkts/sec)
TRTL: throttle count

Interface                IHQ  IQD  OHQ  OQD  RXBS  RXPS  TXBS  TXPS  TRTL
-----
FastEthernet0/0          0    0    0    0    0    0    0    0    0
```

```
NOTE:No separate counters are maintained for subinterfaces
```

```
Hence Details of subinterface are not shown
```

```
Router#configure terminal
```

```
Enter configuration commands, one per line. End with CNTL/Z.
```

```
Router(config)#hostname r1
```

```
r1(config)#int
```

```
r1(config)#interface fa0/0
```

```
r1(config-if)#ip addr 192.0.2.1 255.255.255.0
```

```
r1(config-if)#no sh
```

```
00:06:09: %LINK-3-UPDOWN: Interface FastEthernet0/0, changed state to up
```

```
r1(config-if)#do sh run | section interface
```

```
interface FastEthernet0/0
```

```
ip address 192.0.2.1 255.255.255.0
```

```
duplex half
```

```
r1(config-if)#
```